

C-64 Lumberyard Fires

Emergency Manual

Date Revised: 02/01/2018

Last Modified: 09/27/2024 09:54

Export C64 to PDF
Export -Entire C Manual- to PDF

Policy/Procedure

- 1. The first unit on scene shall establish Command and give a condition report including extent of fire.
- **2.** As lumberyard fires typically spread rapidly, Command shall consider additional equipment, manpower, and water supply early in the fire.
- **3.** Fire personnel shall lay supply lines as needed. Initial fire streams from $2\frac{1}{2}$ " or larger hoselines shall be initially placed on the leeward (down wind) side of the fire to prevent fire spread.
 - **NOTE:** It is understood that this may be a punishing position to operate from; however, it is usually the best tactical position on the fireground. Fire personnel operating from such a position shall identify escape routes in advance and be prepared to utilize those routes at any time. Fire personnel shall not operate from positions of entrapment.
- **4.** If possible, the initial attack shall be made on exposed piles of lumber and buildings that are threatened. Later arriving companies shall attack the main body of fire.
 - **NOTE:** It is important to get ahead of the fire, especially if the wind is a factor.
- **5.** Command shall request the response of additional units to patrol the area for spot fires.
 - **NOTE:** These fires can produce flying brands and sparks that can start fires a considerable distance away.
- **6.** During overhaul, crews shall be mindful of the potential collapse of piles of lumber. Bulldozers or end-loaders will be helpful in turning over piles that need to be fully extinguished.

See Also:

Permanent link:

 $https://www.tfrdweb.com/dokuwiki/doku.php?id = c_manual:c64$

Last update: 09/27/2024 09:54

